





Product Code 540

Made In

China













Distributed by: Saurya HSE Pvt Ltd T: +91 22 4065 5555 | E: commercial@sauryahse.com | W: sauryahse.com INSTRUCTIONS FOR USE

Liner	HPPE/Glass Fiber
Coating	Nitrile

Caution

- · Designed to protect against mechanical risks.
- Do not use in places with chemical, thermal or electrical hazards.
- · Gloves are designed to fit to the hand and therefore the glove length may not meet the requirements of EN ISO 21420:2020.
- Performance levels applicable to the palm of the hand only.
- Do not use in places with entanglement or entrapment risks, such as rotating machinery.
- For donning, check the integrity of the glove and that the picked size fits the hand. For doffing, ease off the glove of one hand before removing the second glove to reduce the risk of contamination.
- Before use, inspect the glove for any defects or imperfections.
- · Contains zinc pyrithione.

Storage

· Store in a dry place away from direct sunlight and humidity.

Cleaning

· Clean with a damp cloth to remove excess contamination.

Date of Obsolescence

• When stored correctly, the mechanical properties do not change. The glove's useful life cannot be specified as it depends on the applications and the user's responsibility.

2

EN388:2016 +A1:2018

abcde

Level	1	2	3	4	5
a: Abrasion	100	500	2000	8000	N/A
b: Cut (Coupe Test)	1.2	2.5	5.0	10.0	20.0
c: Tear	10	25	50	75	N/A
d: Puncture	20	60	100	150	N/A
Level	Α	В	С	D	Е

10

15

22

30

X=Not tested

e: Cut (ISO)

EN