

PARALUX® PX1

sturdy flashlight, suitable for Zone 0, with powerful luminance



Part denomination	PARALUX® PX1
Part number	6911252158
GTIN /EAN	4006793749788
customs tariff number	85131000
Country of origin	CN
Fittings	<ul style="list-style-type: none"> - flashlight ATEX and IECEx certified for Zone 0 / 21 - 100 % watertight - polycarbonate with antistatic additive - rubberized lamp head - rubberized rear switch for one-hand operation - lamp: CREE LED XT-E (5W) - luminance: approx. 120 lumens - headlight range: approx. 150 m - battery type: 4x AA/Mignon/each 1.5 V - supplied in blister packaging including batteries - compatible with almost all helmet mounts and with our PARASNAP®
Scope of delivery	<ul style="list-style-type: none"> - 4x AA/Mignon/each 1.5 V - user manual
Dimensions (WxDxH)	167 mm x 41 mm x 43 mm
Weight	80 g
gross weight (incl. batteries)	185 g
Protection class	<ul style="list-style-type: none"> - II 1G Ex ia IIC T4 Ga - II 2D Ex ib IIIC T105°C Db IP68
Bulb	CREE LED XT-E (5W)
Light flux	approx. 120 lumens
Light range	approx. 150 meters
Running time	approx. 15 hours full power, a total of approx. 50 hours
Material Licht	PC (polycarbonate)
Color Licht	yellow

product image similar / information without content / subject to errors and changes / all dimensions in mm