

ATEXOR order code	SHNL2LED...	
Product description	Explosion protected luminary for portable use	
ATEX, IECEx and UKEX marking	Ex II 2 G Ex eb mb op is IIC T4 Gb Ex II 2 D Ex tb op is IIIC T90°C Db	
Temperature classification	T4 (internal) T90°C (external)	
Operating temperature	-40°C ... +55°C	
Light source	2 Led modules with SafeEye® technology	
Light emitted at source	5650 lm	
Luminous flux (measured)	3140 lm	
Colour temperature	4600 - 5700 K	
Colour rendering index	>80	
Photobiological safety	Exempt group (No marking required, safe in normal use)	
Supply Voltage	100-250VAC/DC, 0/ 50/60Hz or 20-50VAC /DC, 0/50/60Hz	
Supply Current (typical)	230V~0,25 A 110V~0,5 A	42V~1,2 A 24V~2,1 A
Electrical class	Class 1 (230 VAC), Class 3 (20-50V)	
Power	< 50 W	
Cable	Standard cable H07BQ-F	
Plug and socket	2P+E (110-230V) 2P+E, 3P, 2P (24-42V) ATX, CEAG	
Enclosure	Dissipative materials (PC & TPE)	
Ingress protection	IP66	
Weight (without cable, plug and socket)	3,4 kg	
Accessories	SLAM Click'n Fix magnetic fixing system Protective film	





Datasheet

SLAM Hornet Neos Linear 2LED

Product model	Dimensions / mm	
	L	Ø
SLAM® Hornet Neos Linear 2LED	1040	125

