




Manufacturing date	Q3/2021
Certification marking	 II 2 GD Ex db eb IIC T4/T3 Gb Ex tb IIIC T90°C Db  Dust approval subject to socket type.
Product description	Explosion protected portable or transportable transformer
Temperature classification	T3 or T4
Operating temperature	-20°C ... +55°C
Supply Voltage (min-max)	110V, 230V +/- 6%
Supply Current typical	2A or 4A
Output voltage	12VAC, 24VAC or 42VAC
Output current	Max. 16A
Number of outputs	Low voltage: 2 or 4 Low voltage: 3 + 1 mains for linking
Electrical class	Class I
Maximum load	42VAC 384W 24VAC 384W 12VAC 192W
Cable	H07RN-F, H07BQ-F or H-Flex
Plug and socket options	ATX, CEAG, Marechal, Stahl Mains linkable available only with ATX, Marechal and Stahl sockets and plugs.
Enclosure	Aluminium case, stainless steel frame
Ingress protection	IP66
Weight (without cable and plug)	19kg (incl. 4x sockets)
Warranty	You will find detailed warranty conditions from <a href="http://www.atexor.com/downloads/">http://www.atexor.com/downloads/</a>

	Dimensions / mm		
	L	W	H
SLAM® TrafoEX	585	295	310



**SAURYA**

Value Driven Safety

Distributed by: Saurya HSE Pvt Ltd  
HO: C-112 A Kailash Business Park, Veer Sawarkar Marg, Vikhroli West, Mumbai 400079, India  
T: +91 22 4065 5555 | E: [info@sauryahse.com](mailto:info@sauryahse.com) | W: [sauryahse.com](http://sauryahse.com)