

COPPUS Marine Ventilators

Steam-, air- and water turbine-drive ventilators

Water turbine-drive for
air supply or exhaust

Steam- or
compressed
air-turbine
drive for air
supply or
exhaust



MODEL/SPECIFICATIONS

STEAM/COMPRESSED AIR TURBINE DRIVES

MODEL C-12A

SUPPLY Model

delivers 5,350 cfm (9,090 m³/hr)

EXHAUST Model

delivers 4,600 cfm (7,815 m³/hr)

MODEL C-15A

SUPPLY Model

delivers 8,400 cfm (14,275 m³/hr)

EXHAUST Model

delivers 6,500 cfm (11,044 m³/hr)

WATER TURBINE DRIVES

MODEL C-12AWC

SUPPLY Model

delivers 5,000 cfm (8,495 m³/hr)

EXHAUST Model

delivers 4,700 cfm (7,985 m³/hr)

MODEL C-15AWC

SUPPLY Model

delivers 7,400 cfm (12,573 m³/hr)

EXHAUST Model

delivers 5,700 cfm (9,769 m³/hr)



Available adapters for:

- Butterworth deck and tank opening (pictured)
- Duct adapter

SAFETY PRECAUTIONS

Always be sure unit is connected to a suitable ground connection. Mounting on non-conductive adapters or free-standing use requires a bonding cable.

DESCRIPTION

These rugged, dependable cargo tank ventilators have served the shipping industry for many years. They are ideal for on-board gas-freeing, drying and ventilation operations and are available in supply or exhaust models.

STEAM/COMPRESSED AIR TURBINE-DRIVE MODELS FEATURES / ADVANTAGES

- Cast iron turbine housing with aluminum cover
- Bronze turbine wheel
- Grease-type ball bearings
- Cast aluminum fan and fan casing
- Stainless steel fasteners, mounting studs and protective screen



WATER TURBINE-DRIVE MODELS FEATURES / ADVANTAGES

- Cast aluminum anodized turbine housing
- Cast aluminum anodized impeller
- Cast aluminum inlet and outlet water connections
- Grease-sealed stainless steel ball bearings
- Cast aluminum fan and fan casing
- Stainless steel fasteners and protective screen

DIMENSIONS

MODEL	in/mm								NET* WT lbs/kg
	A	B	C	D	E	F	BOLT SLOTS		
							SIZE	NO.	
C-12A	12.6 321	14.2 362	20.5 521	12.5 318	15.3 390	16.8 427	0.93 24	10	100 45
C-15A	21.0 533	14.2 362	22.2 565	15.3 387	20.5 521	21.5 546	1.12 28	8	120 54
C-12AW	14.8 376	14.2 362	22.5 572	12.5 318	15.3 390	16.8 427	0.93 24	10	63 28
C-15AW	16.5 419	14.2 362	24.5 622	15.2 387	20.5 521	21.5 546	1.12 28	8	77 35

*Net weights shown are supply units.



For more information about Coppus portable ventilation products, contact us at:

Saurya HSE Pvt Ltd

HO: C-112 A, Kailash Business Park, Veer Sawarkar Marg, Vikhroli West, Mumbai, Maharashtra 400079

T: +91 22 4065 5555 | E: info@sauryahse.com | W: sauryahse.com