

Manufacturing date	22.08.2014 –
Product description	Portable luminary with explosion protection
ATEX marking	Ex II 2 GD Ex e mb IIC T4 Gb Ex tb IIIC T 90 °C Db
Temperature classification	T4 (< 135 °C)
Operating temperature	0°C ... +55°C
Light source	Fluorescent tube
Light output (Light source)	Approx. 4110 lm (2x22 W) Approx. 2050 lm (1x22 W)
Colour temperature	4000 K
Colour rendering index	>80
Photobiological safety	Exempt group (No marking required, safe in normal use)
Supply Voltage	230VAC +/- 6%, 50/60Hz or 110 VAC +/- 6%, 50/60Hz 24 VAC +/- 6%, 50/60Hz
Supply Current (typical)	230 V~0,2 A ;110 V~0,4 A 24 VAC ~1 A (1x22 W) ; 24 VAC~2 A (2x22 W)
Electrical class	Class I (230 V & 110 V) Class III (24 V)
Power	22 W / 44 W
Cable	H07BQ-F
Plug	2P + Earth
Enclosure	Dissipative materials (PC & TPE)
Ingress protection	IP66
Weight (without cable, socket and plug)	1,65 kg (1x22W) 2,85kg (2x22 W)
Accessories	SLAM Click'n Fix magnetic fixing system
Warranty	You will find detailed warranty conditions from www.atexor.com/warranty

Product model	Dimensions / mm		Variables
	L	Ø	
SLAM® Hornet 2x22 W HT	860	115	A-variable = Cable in
SLAM® Hornet 1x22 W HT	576	115	C-variable = Cable in, socket out

